



Site Hoists

Scaffold Hoist

- Simple and quick to erect
- Rapid hoisting speed at full load
- Work positioning lever
- Scaffold fixing attachment included
- Lifting buckets and cages available

Product Code	Model	Maximum Capacity (kg)	Average Full Load Lifting Speed (m/min)	Maximum Working Height (m)	Diameter of Steel Rope (mm)	Rope Length (m)	Motor Power Rate (kW)	Motor Speed (rpm)	Running Current (A)	Machine Weight (kg)	SPL in Operator's Position (dB(A))	Dimensions (W/L closed (open) /H) (mm)	Packaging Dimensions W/L/H (mm)
H010300200	TR225N	200	19	30	5	30	0.75 (230V/50Hz) (110V/50Hz)	1360 /1380	14/7.2	44/46	<70	330 / 770 (1170) / 520	350 / 820 / 500



Builder's Gantry Hoists & Monorail Beams

- Frame with built-in 4 wheel trolley to traverse the hoist
- Positioning brake
- Top limit switch
- Lifting hook secured by self locking clamp
- Rear mounted bracket boxes, each require 50% of the maximum rated load capacity of the hoist
- Separate Monorail Beam also available with scaffold suspension fittings (Capacity 500kg) – Product code: H010510005

Product Code	Model	Maximum Capacity (kg)	Average Full Load Lifting Speed (m/min)	Maximum Working Height (m)	Diameter of Steel Rope (mm)	Rope Length (m)	Motor Power Rate (kW)	Motor Speed (rpm)	Running Current (A)	Machine Weight (kg)	SPL in Operator's Position (dB(A))	Dimensions (W/L/H) (mm)	Packaging Dimensions W/L/H (mm)
H580200300	ET300	300	19	30	5	31	1.1 (110V/50Hz)	1320	18 (110V)	50	<75	330 / 780 / 380	350 / 820 / 440
H580200500	G500	500	17	4	6	43	1.5 (110V/50Hz)	1320	23	50	<72	382 / 800 / 410	400 / 820 / 440

Accessories



Two Bucket Carrier



Four Bucket Carrier



Wedge Shaped Bucket



Liftable Wheelbarrow



External Prop & Ballast Box

